

Cutting Power

A new angle that's distinctively KaVo Superlative Performance. Cutting performance, higher precision, increased access and safer preparations are some of the many benefits of SURGtorque Air-driven handpieces.



Cutting Power

The SURGtorque features 19 Watts of cutting power to improve efficiency and minimize bur stalls.



MULTI-flexibility

To improve ergonomics and safety, every dental coupler features 360° full rotation with a quick disconnect and a built-in anti-retraction valve.



Increased Access

The SURGtorque features a 45 degree angled head for increased access in the molar regions.



Safe Preparations

The SURGtorque features air exhausts through the back cap and through exhaust vents on the sides for improved patient safety.



Hygienic Design

The SURGtorque features a durable hygienic coating with textured surface for easy grip and easy cleaning.



PRODUCT FEATURES AND BENEFITS

		
SURGtorque	S459 L	S459 C
Head size	Standard	Standard
Features	19 Watts, single port water with no spray	
Part no.	3000.4808	3000.5063

The KaVo SURGtorque LUX S459 features 19W at 2,8 bar of cutting power for increased efficiency and faster preps. Side and rear exhaust to help increase patient safety, and enduring KaVo quality.

With its uniquely angled head, increased access is simple. Experience for yourself, the difference between ordinary and extraordinary.

Cutting Power

Enhanced by their computer balanced turbine, carbide lined chuck for more concentric cutting and smoother, more precise preps.

Increased Access

Including a hygienic design that helps increase patient safety.

MUTLIflexibility

The anti-retraction valve prevents the backflow of potentially contaminated water into the tubing. With the KaVo MULTIflex handpiece coupler in your practice, “just a click does the trick!”

Safe Preparations

Also with one port stream for improved performance.



460LED MULTIflex™ LUX Coupler

Part no. 1007.3201




1390 MULTIflex LUX Coupler

Part no. 0553.1390



465LED MULTIflex LUX Coupler

Part no. 1007.3197



457 MULTIflex Coupler

Part no. 0553.1210

INDICATIONS FOR USE

SURGtorque E459 L

- 45° head angle for improved access to molar region
- Fiber optic
- Powerful 19W turbine for increased efficiency
- MULTIflex connection
- Ceramic Bearings
- Exhaust ports direct excess exhaust away from the cutting area
- Single port water with no spray
- Push button auto chuck
- Accepts standard and surgical length burs
- 1-year warranty
- 380,000 rpm
- Recommended air pressure 41 psi (2.8 bar)

SURGtorque E459 C

- 45° head angle for improved access to molar region
- Non-optic
- Powerful 19W turbine for increased efficiency
- Standard 4-hole connection
- Ceramic Bearings
- Exhaust ports direct air away from the cutting area
- Single port water with no spray
- Push button auto chuck
- Accepts standard and surgical length burs
- 1-year warranty
- 420,000 rpm
- Recommended air pressure 41 psi (2.8 bar)